




FEATURES



Non Reflective



Quick Dry time



Faster Installation



Higher Thickness



5 to 55% VLT Range

NR QUICK DRY PLUS
FILM

VARIANT	PLY	THICKNESS (MIL)	VISIBLE LIGHT TRANSMISSION (VLT)	GLARE REDUCTION (GR)	ULTRAVIOLET REJECTED (UVR)	VISIBLE LIGHT REFLECTANCE EXTERIOR (VLR-E)	TOTAL SOLAR ENERGY REJECTED (TSER)
NR QUICK DRY PLUS 55	2	1.5	55%	40%	>99%	7%	29%
NR QUICK DRY PLUS 50	2	1.5	49%	46%	>99%	6%	30%
NR QUICK DRY PLUS 45	2	1.5	45%	51%	>99%	6%	32%
NR QUICK DRY PLUS 40	2	1.5	39%	57%	>99%	6%	33%
NR QUICK DRY PLUS 35	2	1.5	35%	62%	>99%	6%	34%
NR QUICK DRY PLUS 30	2	1.5	30%	67%	>99%	6%	35%
NR QUICK DRY PLUS 20	2	1.5	19%	79%	>99%	6%	40%
NR QUICK DRY PLUS 15	2	1.5	16%	82%	>99%	6%	41%
NR QUICK DRY PLUS 05	2	1.5	6%	93%	>99%	6%	42%