



RS 20 Extern Polycarbonaat


Sun protection privacy film External.

SKU: REZ1505


GSW® RS 20 External Polycarbonate self-adhesive reflective window film is specially designed to protect against the harmful effects of sunlight: it blocks solar heat, reduces reflection and prevents discolouration of polycarbonate and other synthetic materials. Can be used on a flat surface.

Features:

- Blocks infrared High.
- Creates a beautiful appearance on the skylight.
- Ideal against prying eyes during the day.
- Surface gets a longer lifespan.
- Silver glass look.
- View from inside to outside.



PRODUCT PERFORMANCE	
UV protection	99%
Light transmission	16%
Reflection of visible light outside	62%
Reflection of visible light inside	60%
Reflection of solar energy	67%
Absorption of solar energy	20%
Transmission of solar energy	13%
Reduction of reflection	84%
Sun transmission	11%
Rejected solar energy single glazing	89%
Rejected solar energy double glazing	89%
G-value	0.18
U-value single	5.1
U-value double	
Shade coefficient	0.2
Infrared rejection (760-2500 nm)	



*

PROFESSIONAL WINDOWFILM
VISIT **GSWFILM.COM**

Contact sales +31 (0)299-323122 info@gswfilm.com



RS 20 Extern Polycarbonaat

Sun protection privacy film External.

SKU: REZ1505

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	NB !
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	no
Reflective tinted double pane	Yes
Gas-filled double pane - Low E	NB !
Stadip ext. clear double pane	Yes
Stadip int. clear double pane	Yes
Triple glazed	no
Acrylic 4 mm	Yes
Polycarbonate 4 mm	yes, Channel plates no.

*Recommendations based on a glass surface of max. 2.5 m2. Contact us for further information.

U-value

The lower the U-value, the better the thermal resistance of the window film, meaning less heat is lost to the outside.

PRODUCT FEATURES	
Width(s)	122 and 152 cm
Length(s)	30 meters
Film thickness	65 µ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to +40 °C
Fire class	EN13501-1
Energy performance	EN 410
Manufacturer	


Installation

Install window film with water and Servfaces® Slip.

Absolutely do not use chemical agents!

Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with Servfaces® Fast Shine - 3 in ONE. Be careful not to use chemicals!



1. Hard scratch-resistant layer for long life and ease of maintenance when cleaning the windows.
2. Optically high-quality polyester, with metal particles against IR radiation.
3. Self-adhesive glue, glass polymerization within 15 days.
4. Protective film, disposable after installation.

PROFESSIONAL WINDOWFILM
VISIT [GSWFILM.COM](https://www.gswfilm.com)

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW

Glass Solution Windowfilm B.V. Schepnetstraat 3a, 1446 AL Purmerend +31 (0)299-323 122 info@gswfilm.com



FREE SAMPLE

SOLAR

V17/07/26