



# Eco Windowfilm 35


Insulating window film.

SKU: RS1578

The sputtered polyester GSW® Eco Windowfilm series window film consists of several metal layers and provides thermal insulation. In summer, excessive heat does not enter through the glass and in winter heat loss is limited. So a lower U-value. When this insulating high-efficiency window film is applied to your windows, it provides significant cost savings for heating and air conditioning, quickly recouping the initial costs of purchase and installation.

#### Features:


- Positive Insulating function.
- Also keeps your energy costs low.
- Neutral appearance.
- Limitation of double glazing heat loss 50%.
- Sun protection during warm periods.
- UV werend voor uw interieur.



SOLAR

#### PRODUCT PERFORMANCE

UV protection	99%
Light transmission	45%
Reflection of visible light outside	37%
Reflection of visible light inside	40%
Reflection of solar energy	38%
Absorption of solar energy	30%
Transmission of solar energy	32%
Reduction of reflection	55%
Sun transmission	50%
Rejected solar energy single glazing	50%
Rejected solar energy double glazing	66%
G-value	0.35
U-value single	4.2
U-value double	2.2
Shade coefficient	0.4



Warranty	6 years
Installation	Inside
Foil colour	Light Silver

**PROFESSIONAL WINDOWFILM**  
VISIT [GSWFILM.COM](http://GSWFILM.COM)

Contact sales +31 (0)299-323122 [info@gswfilm.com](mailto:info@gswfilm.com)

# Eco Windowfilm 35

Insulating window film.

SKU: RS1578

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	No
Reflective tinted double pane	No
Gas-filled double pane - Low E	No
Stadip ext. clear double pane	No
Stadip int. clear double pane	No
Triple glazed	No
Acrylic 4 mm	Yes
Polycarbonate 4 mm	No

PRODUCT FEATURES	
Width(s)	152 cm
Length(s)	30 meters
Film thickness	50 μ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to '+40 °C
Fire class	EN13501-1
Manufacturer	

## Installation

Install the film with water and green Fairy dishwashing liquid. Under no circumstances use chemicals!

## Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with water and green Fairy dishwashing liquid. Be careful not to use chemicals!

\*Recommendations based on a glass surface of max. 2.5 m<sup>2</sup>. Contact us for further information.

## U-value

The lower the U-value, the better the thermal resistance of the foil, with less heat being lost to the outside.



1. Hard scratch-resistant layer for a long lifespan and ease of maintenance when cleaning the windows.
2. Optical high-quality polyester, with metal particles against IR radiation.
3. Self-adhesive glue, glass polymerization within 15 days.
4. Protective film, disposable after installation.

**PROFESSIONAL WINDOWFILM**  
VISIT [GSWFILM.COM](http://GSWFILM.COM)

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (\*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW



**FREE SAMPLE**