



Grey RS 10 Extern


Sun protection privacy film External.

SKU: REZ1508


GSW® Grey RS 10 External window film keeps solar heat to a minimum and at the same time allows some natural light. Light reflection is effectively counteracted and because the film acts as a one-way mirror, it is not possible to look inside. Buildings immediately get a modern look with this film.

Features:

- Blocks infrared High.
- Creates an attractive appearance on the facade.
- Ideal against prying eyes during the day.
- Glass will have a longer lifespan.
- Do you want to block out just a little more light than normal?



PRODUCT PERFORMANCE	
UV protection	99%
Light transmission	10%
Reflection of visible light outside	64%
Reflection of visible light inside	12%
Reflection of solar energy	61%
Absorption of solar energy	31%
Transmission of solar energy	8%
Reduction of reflection	90%
Sun transmission	14%
Rejected solar energy single glazing	82%
Rejected solar energy double glazing	86%
G-value	0.17
U-value single	5.1
U-value double	
Shade coefficient	0.2



Warranty vertical*	5 years
Warranty horizontal*	3 years
Installation	outside
Foil colour	Silver
Foil colour inside	Dark blue

* Window film under cover strip or use tested Bloem® sealing products.

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

Contact sales +31 (0)299-323122 info@gswfilm.com

Grey RS 10 Extern

Sun protection privacy film External.

SKU: REZ1508

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	Yes
Reflective tinted double pane	Yes
Gas-filled double pane - Low E	Yes
Stadip ext. clear double pane	NB !
Stadip int. clear double pane	Yes
Triple glazed	Yes
Acrylic 4 mm	Yes
Polycarbonate 4 mm	no

*Recommendations based on a glass surface of max. 2.5 m2. Contact us for further information.

U-value

The lower the U-value, the better the thermal resistance of the window film, meaning less heat is lost to the outside.

PRODUCT FEATURES	
Width(s)	152 cm
Length(s)	30 meters
Film thickness	60 μ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to +40 °C
Fire class	EN13501-1
Manufacturer	

Installation

Install the film with water and green Fairy dishwashing liquid. Under no circumstances use chemicals!

Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with water and green Fairy dishwashing liquid. Be careful not to use chemicals!



1. Hard scratch-resistant layer for long life and ease of maintenance when cleaning the windows.
2. Optically high-quality polyester, with metal particles against IR radiation.
3. Self-adhesive glue, glass polymerization within 15 days.
4. Protective film, disposable after installation.

PROFESSIONAL WINDOWFILM
VISIT **GSWFILM.COM**

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW

Glass Solution Windowfilm B.V. Schepnetstraat 3a, 1446 AL Purmerend +31 (0)299-323 122 info@gswfilm.com



FREE SAMPLE