



# Mirror 05


Sun protection privacy film Internal

SKU: RS1541


**GSW® Mirror 05 is very effective in reducing Prying eyes also called a heavy confrontation mirror window film and the one way mirror aspect guarantees privacy from prying eyes while giving a modern look. Product is also used to create a real mirror.**

**Features:**

- Blocks infrared High.
- Creates an attractive appearance on the facade.
- Ideal against prying eyes.
- Glass gets a longer lifespan.
- Silver glass look.
- Dark view from the inside out.



PRODUCT PERFORMANCE	
UV protection	99%
Light transmission	5%
Reflection of visible light outside	60%
Reflection of visible light inside	60%
Reflection of solar energy	62%
Absorption of solar energy	33%
Transmission of solar energy	4%
Reduction of reflection	96%
Sun transmission	17%
Rejected solar energy single glazing	87%
Rejected solar energy double glazing	83%
G-value	0.09
U-value single	5.1
U-value double	
Shade coefficient	0.1



Warranty	10 years
Installation	Inside
Foil colour	Silver

**PROFESSIONAL WINDOWFILM**  
**VISIT [GSWFILM.COM](http://GSWFILM.COM)**

Contact sales +31 (0)299-323122 [info@gswfilm.com](mailto:info@gswfilm.com)

# Mirror 05

Sun protection privacy film Internal

SKU: RS1541

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	No
Tinted double pane	No
Reflective tinted double pane	No
Gas-filled double pane - Low E	No
Stadip ext. clear double pane	No
Stadip int. clear double pane	No
Triple glazed	No
Acrylic 4 mm	Yes
Polycarbonate 4 mm	No

PRODUCT FEATURES	
Width(s)	152 cm
Length(s)	30 meters
Film thickness	60 μ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to '+40 °C
Fire class	EN13501-1
Manufacturer	

\*Recommendations based on a glass surface of max. 2.5 m2. Contact us for further information.

### U-value

The lower the U-value, the better the thermal resistance of the foil, with less heat being lost to the outside.

### Installation

Install the film with water and green Fairy dishwashing liquid. Under no circumstances use chemicals!

### Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with water and green Fairy dishwashing liquid. Be careful not to use chemicals!



1. Hard scratch-resistant layer for long life and ease of maintenance when cleaning the windows.
2. Optically high-quality polyester, with metal particles against IR radiation.
3. Self-adhesive glue, glass polymerization within 15 days.
4. Protective film, disposable after installation.

**PROFESSIONAL WINDOWFILM**  
VISIT **GSWFILM.COM**

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (\*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW



**FREE SAMPLE**