



R-Bronze 10


Sun protection privacy film Internal

SKU: RZ1506

GSW® R-Bronze 10 window film keeps solar heat to a minimum and at the same time guarantees a maximum of natural light. With this film, the reflection of sunlight is significantly reduced and buildings gain color and personality.


Features:

- Blocks infrared High.
- Creates an attractive appearance on the facade.
- Ideal against prying eyes during the day.
- Glass gets a longer lifespan.
- Dark bronze glass look.
- View from inside to outside.



PRODUCT PERFORMANCE

UV protection	99%
Light transmission	12%
Reflection of visible light outside	18%
Reflection of visible light inside	60%
Reflection of solar energy	34%
Absorption of solar energy	57%
Transmission of solar energy	9%
Reduction of reflection	91%
Sun transmission	24%
Rejected solar energy single glazing	72%
Rejected solar energy double glazing	76%
G-value	0.23
U-value single	5.1
U-value double	
Shade coefficient	0.2



SOLAR

Warranty	10 years
Installation	Inside
Foil colour	Dark Bronze

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

Contact sales +31 (0)299-323122 info@gswfilm.com

R-Bronze 10

Sun protection privacy film Internal

SKU: RZ1506

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	No
Reflective tinted double pane	No
Gas-filled double pane - Low E	No
Stadip ext. clear double pane	No
Stadip int. clear double pane	No
Triple glazed	No
Acrylic 4 mm	Yes
Polycarbonate 4 mm	No

PRODUCT FEATURES	
Width(s)	152 cm
Length(s)	30 meters
Film thickness	40 μ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to '+40 °C
Fire class	EN13501-1
Manufacturer	

Installation

Install the film with water and green Fairy dishwashing liquid. Under no circumstances use chemicals!

Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with water and green Fairy dishwashing liquid. Be careful not to use chemicals!

*Recommendations based on a glass surface of max. 2.5 m2. Contact us for further information.

U-value

The lower the U-value, the better the thermal resistance of the foil, with less heat being lost to the outside.



1. Hard scratch-resistant layer for long life and ease of maintenance when cleaning the windows.
2. Optically high-quality polyester, with metal particles against IR radiation
3. Self-adhesive glue, glass polymerization within 15 days.
4. Protective film, disposable after installation

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW



FREE SAMPLE