



SP Steel 20 Super Plus Extern


Sun protection privacy film External.

SKU: REZ1814

GSW® SP Steel 20 Super Plus External window film keeps solar heat to a minimum and at the same time allows some natural light. With this film, the reflection of sunlight is significantly reduced and buildings get color and personality. View from inside to outside is very neutral.


Features:

- Blocks infrared Normal.
- Creates a beautiful appearance on the facade.
- Ideal against prying eyes during the day.
- Glass gets a longer lifespan.
- Steel glass look
- The latest technology.



PRODUCT PERFORMANCE

UV protection	99%
Light transmission	22%
Reflection of visible light outside	32%
Reflection of visible light inside	28%
Reflection of solar energy	31%
Absorption of solar energy	49%
Transmission of solar energy	20%
Reduction of reflection	80%
Sun transmission	27%
Rejected solar energy single glazing	69%
Rejected solar energy double glazing	73%
G-value	0.3
U-value single	5.8
U-value double	
Shade coefficient	0.3



SOLAR

Warranty vertical*	8 years
Warranty horizontal*	5 years
Installation	outside
Foil colour	Steel
Foil colour inside	

* Window film under cover strip or use tested Bloem® sealing products.

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

Contact sales +31 (0)299-323122 info@gswfilm.com



SP Steel 20 Super Plus Extern

Sun protection privacy film External.

SKU: REZ1814

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	Yes
Reflective tinted double pane	Yes
Gas-filled double pane - Low E	Yes
Stadip ext. clear double pane	no
Stadip int. clear double pane	Yes
Triple glazed	no
Acrylic 4 mm	Yes
Polycarbonate 4 mm	no

PRODUCT FEATURES	
Width(s)	122, 152 and 183 cm
Length(s)	30 meters
Film thickness	60 μ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to +40 °C
Fire class	EN13501-1
Manufacturer	

*Recommendations based on a glass surface of max. 2.5 m2. Contact us for further information.

U-value


The lower the U-value, the better the thermal resistance of the window film, meaning less heat is lost to the outside.

Installation

Install the film with water and green Fairy dishwashing liquid. Under no circumstances use chemicals!

Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with water and green Fairy dishwashing liquid. Be careful not to use chemicals!



1. Hard scratch-resistant layer for long life and ease of maintenance when cleaning the windows.
2. Optically high-quality polyester, with metal particles against IR radiation.
3. Self-adhesive glue, glass polymerization within 15 days.
4. Protective film, disposable after installation.

PROFESSIONAL WINDOWFILM
VISIT **GSWFILM.COM**

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW



FREE SAMPLE