



Sp Steel 35


Sun protection privacy film Internal

SKU: RZ1515

GSW® Sp Steel 35 window film keeps solar heat to a minimum and at the same time allows some natural light. Thanks to its neutral colour, this film is a discreet solution that limits solar heating

Features:

- Block infrared Medium.
- Creates an attractive appearance on the facade.
- Minimum privacy screen allows more light to pass through.
- Glass gets a longer lifespan.
- Steel glass look.
- Quiet window film.



PRODUCT PERFORMANCE

UV protection	99%
Light transmission	43%
Reflection of visible light outside	17%
Reflection of visible light inside	14%
Reflection of solar energy	16%
Absorption of solar energy	46%
Transmission of solar energy	38%
Reduction of reflection	51%
Sun transmission	50%
Rejected solar energy single glazing	48%
Rejected solar energy double glazing	50%
G-value	0.34
U-value single	5.65
U-value double	
Shade coefficient	0.3

99%



UV

43%



LTA

48%



AZ-EG

46%



ABS

SOLAR

Warranty

10 years

Installation

Inside

Foil colour

Medium Steel

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

Contact sales +31 (0)299-323122 info@gswfilm.com

Sp Steel 35

Sun protection privacy film Internal

SKU: RZ1515

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	No
Reflective tinted double pane	No
Gas-filled double pane - Low E	No
Stadip ext. clear double pane	No
Stadip int. clear double pane	No
Triple glazed	No
Acrylic 4 mm	Yes
Polycarbonate 4 mm	No

PRODUCT FEATURES	
Width(s)	152 and 183 cm
Length(s)	30 meters
Film thickness	50 μ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to '+40 °C
Fire class	EN13501-1
Manufacturer	

*Recommendations based on a glass surface of max. 2.5 m2. Contact us for further information.

U-value

The lower the U-value, the better the thermal resistance of the foil, with less heat being lost to the outside.

Installation

Install the film with water and green Fairy dishwashing liquid. Under no circumstances use chemicals!

Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with water and green Fairy dishwashing liquid. Be careful not to use chemicals!



1. Hard scratch-resistant layer for long life and ease of maintenance when cleaning the windows.
2. Optically high-quality polyester, with metal particles against IR radiation.
3. Self-adhesive glue, glass polymerization within 15 days.
4. Protective film, disposable after installation.

PROFESSIONAL WINDOWFILM
VISIT **GSWFILM.COM**

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW



FREE SAMPLE