



CC003 Yellow


Colour raamfolie

SKU: RK1552


GSW® CC003 Crystal Clear Green Window Film allows you to give glass a color and leave transparency completely intact. It is the perfect way to give interior glass such as partition walls, shower screens, glass system walls and the like a colorful appearance.

Features:

- Turns your environment into a wink.
- Creates a beautiful appearance.
- Glass gets a longer lifespan.
- Do not expose window film to the sunny side.
- Yellow.



PRODUCT PERFORMANCE	
UV protection	99%
Light transmission	85%
Reflection of visible light outside	9%
Reflection of visible light inside	9%
Reflection of solar energy	9%
Absorption of solar energy	18%
Transmission of solar energy	73%
Reduction of reflection	5%
Sun transmission	75%
Rejected solar energy single glazing	22%
Rejected solar energy double glazing	25%
G-value	
U-value single	5.7
U-value double	
Shade coefficient	



COLORS

Warranty	Warranty 3 years not on sunny side.
Installation	Inside
Foil colour	Yellow.

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

Contact sales +31 (0)299-323122 info@gswfilm.com

CC003 Yellow

Colour raamfolie

SKU: RK1552

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	Yes
Reflective tinted double pane	no
Gas-filled double pane - Low E	no
Stadip ext. clear double pane	no
Stadip int. clear double pane	no
Triple glazed	no
Acrylic 4 mm	Yes
Polycarbonate 4 mm	no

PRODUCT FEATURES	
Width(s)	152 cm
Length(s)	30 meters
Film thickness	40 µ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to '+40 °C
Fire class	EN13501-1
Manufacturer	

Installation

Install the film with water and green Fairy dishwashing liquid. Under no circumstances use chemicals!

Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with water and green Fairy dishwashing liquid. Be careful not to use chemicals!

***Recommendations based on a glass surface of max. 2.5 m2. Contact us for further information.**

U-value

The lower the U-value, the better the thermal resistance of the foil, with less heat being lost to the outside.



1. Hard scratch-resistant mat layer for long life and ease of maintenance when cleaning the windows.
2. Colored Polyester without optical distortion.
3. Self-adhesive glue, glass polymerization within 15 days.
4. Protective film, disposable after installation.

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW



FREE SAMPLE