



Matte Silver

Privacy

SKU: RA1520

GSW® Matte Silver frosted window film ensures your privacy and infrared radiation because it is impossible to look inside. The film has a silver sun-resistant glass effect and the natural light is largely filtered, creating a subtle ambient light.

Features:

Ideal against prying eyes during the day and in the evening.

Blocks infrared High.

Creates an attractive appearance on the facade.


Glass gets a longer lifespan.

Allows diffuse light to pass through.

Matte and Silver look.



PRODUCT PERFORMANCE	
UV protection	99%
Light transmission	18%
Reflection of visible light outside	60%
Reflection of visible light inside	28%
Reflection of solar energy	56%
Absorption of solar energy	33%
Transmission of solar energy	11%
Reduction of reflection	82%
Sun transmission	20%
Rejected solar energy single glazing	75%
Rejected solar energy double glazing	80%
G-value	0.2
U-value single	5.08
U-value double	
Shade coefficient	0.2



PROFESSIONAL WINDOWFILM
VISIT [GSWFILM.COM](https://www.gswfilm.com)

Contact sales +31 (0)299-323122 info@gswfilm.com



Matte Silver

Privacy

SKU: RA1520

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	no
Reflective tinted double pane	no
Gas-filled double pane - Low E	no
Stadip ext. clear double pane	no
Stadip int. clear double pane	no
Triple glazed	no
Acrylic 4 mm	Yes
Polycarbonate 4 mm	no

***Recommendations based on a glass surface of max. 2.5 m2. Contact us for further information.**

U-value

The lower the U-value, the better the thermal resistance of the foil, with less heat being lost to the outside.


PRODUCT FEATURES	
Width(s)	152 cm
Length(s)	30 meters
Film thickness	60 µ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to '+40 °C
Fire class	EN13501-1
Manufacturer	

Installation

Install the film with water and green Fairy dishwashing liquid. Under no circumstances use chemicals!

Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with water and green Fairy dishwashing liquid. Be careful not to use chemicals!



1. Hard scratch-resistant mat layer for long life and ease of maintenance when cleaning the windows.
2. Optically high-quality Polyester, with metal particles against IR radiation.
3. Self-adhesive glue, glass polymerization within 15 days.
4. Protective film, disposable after installation.

PROFESSIONAL WINDOWFILM
VISIT [GSWFILM.COM](https://www.gswfilm.com)

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW

Glass Solution Windowfilm B.V. Schepnetstraat 3a, 1446 AL Purmerend +31 (0)299-323 122 info@gswfilm.com



FREE SAMPLE

PRIVACY

V29/11/24