



Safety 4 Mil Graffiti

Safety film

SKU: RG1573

GSW® Safety 4 Mil/ Graffiti crystal clear film provides reinforcement of the substrate for temporary solution against anti-fall through, prevents injury, damage and vandalism, testing European standards and guidelines.

Features:

EN 12600 2B2


Injury protection.

NF F31-112.


Anti Graffiti and Vandalism.

Glass will have a longer lifespan.

Completely transparent.



PRODUCT PERFORMANCE	
UV protection	99%
Light transmission	85%
Reflection of visible light outside	11%
Reflection of visible light inside	11%
Reflection of solar energy	14%
Absorption of solar energy	14%
Transmission of solar energy	77%
Reduction of reflection	14%
Sun transmission	81%
Rejected solar energy single glazing	19%
Rejected solar energy double glazing	19%
G-value	0.83
U-value single	5.7
U-value double	
Shade coefficient	0.9



Warranty vertical	5 years
Warranty horizontal	5 years
Installation	Inside and
Foil colour	Transparent
Fire class	EN13501-1

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

Contact sales +31 (0)299-323122 info@gswfilm.com

Safety 4 Mil Graffiti

Safety film

SKU: RG1573

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	Yes
Reflective tinted double pane	Yes
Gas-filled double pane - Low E	Yes
Stadip ext. clear double pane	Yes
Stadip int. clear double pane	Yes
Triple glazed	Yes
Acrylic 4 mm	Yes
Polycarbonate 4 mm	no

PRODUCT FEATURES	
Width(s)	183, 152 and 122 cm
Length(s)	30 meters
Film thickness	120 µ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to +40 °C
Fire class	EN13501-1
Manufacturer	

***Recommendations based on a glass surface of max. 2.5 m2. Contact us for further information.**

U-value

The lower the U-value, the better the thermal resistance of the window film, meaning less heat is lost to the outside.

Installation

Install the film with water and green Fairy dishwashing liquid. Under no circumstances use chemicals!

Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with water and green Fairy dishwashing liquid. Be careful not to use chemicals!



1. Hard scratch-resistant layer for long life and ease of maintenance when cleaning the windows.
2. Optically high quality Polyester.
3. Semi-permanent adhesive makes it easier to remove the film from the substrate.
4. Protective film, disposable after installation.

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW



FREE SAMPLE