



Safety 8 Mil Clear External

Safety film

SKU: RV1573

GSW® Safety 8 Mil Clear External crystal clear film provides reinforcement of the substrate against fall-through, prevents injury, vandalism, quick cracking and explosion hazard according to European standards and guidelines.

Features:

EN 12600 1B1


High injury protection.

EN 356 P1A.


Delaying vandalism, burglary and impact.

Anti Explosion.

Glass will have a longer lifespan.



PRODUCT PERFORMANCE	
UV protection	99%
Light transmission	83%
Reflection of visible light outside	10%
Reflection of visible light inside	10%
Reflection of solar energy	10%
Absorption of solar energy	14%
Transmission of solar energy	76%
Reduction of reflection	15%
Sun transmission	80%
Rejected solar energy single glazing	20%
Rejected solar energy double glazing	21%
G-value	0.82
U-value single	5.7
U-value double	
Shade coefficient	0.9



Warranty vertical	5 Years
Warranty horizontal	3 Years
Installation	Outside
Foil colour	Transparent
Fire class	EN13501-1

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

Contact sales +31 (0)299-323122 info@gswfilm.com

Safety 8 Mil Clear External

Safety film

SKU: RV1573

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	Yes
Reflective tinted double pane	Yes
Gas-filled double pane - Low E	Yes
Stadip ext. clear double pane	Yes
Stadip int. clear double pane	Yes
Triple glazed	Yes
Acrylic 4 mm	Yes
Polycarbonate 4 mm	no

PRODUCT FEATURES	
Width(s)	183 and 152 cm
Length(s)	30 meters
Film thickness	240 μ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to +40 °C
Fire class	EN13501-1
Manufacturer	

***Recommendations based on a glass surface of max. 2.5 m2. Contact us for further information.**

U-value

The lower the U-value, the better the thermal resistance of the window film, meaning less heat is lost to the outside.

Installation

Install the film with water and green Fairy dishwashing liquid. Under no circumstances use chemicals!

Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with water and green Fairy dishwashing liquid. Be careful not to use chemicals!



1. Hard scratch-resistant layer for long life and ease of maintenance when cleaning the windows.
2. Optically high quality Polyester.
3. Reinforced self-adhesive glue for higher elasticity of the film upon impact, polymerization with glass within 30 days.
4. Protective film, disposable after installation.

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW



FREE SAMPLE