PPF & Wrap PREP-Polish

Primer Polish for PPF, Wrap, and Vinyl Films

PPF & Wrap PREP-Polish is a silicone-free, micro-fine primer polish from the fillium product line. It is suitable for all glossy PPF, wrap, and vinyl films. The specially developed formula with additives activates the film's top coat. This allows the coating applied afterward to bond more effectively to the top coat without negatively affecting the properties of the film surface, such as its self-healing capability.

Areas of Application:

- **Glossy PPF, wrap, and vinyl films**
- **Car-wrapping films**
- Vehicle lettering and advertising graphics

Properties:

- Grinding grade: 1
- Gloss grade: 11

Application:

Apply a small amount of PPF & Wrap PREP Polish evenly to the film surface to be treated. Polish the area using a dual-action polisher and an Ultra Fine Cut polishing pad in a crosshatch pattern, first horizontally and then vertically. Work with medium pressure and medium speed throughout the process. At the end, increase both speed and pressure to fully work in the PPF & Wrap PREP Polish. Then remove any residue with a clean microfiber towel, such as the Premium Buffing Towel.

Caution: Do not apply in direct sunlight or allow the product to dry on the surface.

Warning:

Shake well before use. Before application, check suitability and compatibility. Do not apply to hot surfaces, and protect from excessive heat and frost.

Application temperature:	**Storage temperature:**	**Consumption:**	**pH:**
+10°C to +35°C	+10°C to +25°C	8 to 10 ml per m^2	Not determined

Storage and shelf life:

At least 24 months at room temperature when stored upright in tightly closed original containers.

Protect from direct sunlight and freezing temperatures!

Container sizes:

Art. No.:	Container:
SF10519	250 ml
SF10519.1	1000 ml

Accessories: TS 3 PRO Polishing Pad, V3 & V4 Polishing Pads, RT / V3 & V4 Polishing Pads, Premium Buffing Towels, Surface Cleaner PRO

This product information should and can only be taken as non-binding advice. The manufacturer does not accept any liability whatsoever. Before use, make sure that the product is suitable for your particular application.

servFaces GmbH | Zeppelinstr. 2 – 4 | D - 72488 Sigmaringen | Tel.: +49 7571 6894 0 | info@servFaces.de | www.servFaces.de